



MS2115A True RMS 1000A AC/DC DIGITAL CLAMP METER

- 6,000 counts LCD display
- Non-contact AC voltage detection (NCV)
- **In-rush current** function measures starting current for motors, lighting, etc.
- True RMS, Max./Min. and relative measurement
- Clamp-on frequency measurement
- Data hold, clamp light and LCD backlit
- Auto/manual range, auto power off
- Secondary injection molding case, high safety as per IEC1010-1 **Cat.III 1000V & Cat. IV 600V**

Technical specifications

DCV: 60m/600m/6/60/600/1000V, $\pm 0.7\%$

ACV: 60m/600m/6/60/600/750V, $\pm 0.8\%$

DCA: 60/600/1000A, $\pm 2.5\%$

ACA: 60/600/1000A, $\pm 2.5\%$

OHM: 600/6k/60k/600k/6M/60M Ω , $\pm 0.8\%$

CAP: 10n/100n/1000n/10 μ /100 μ /1000 μ /10m/100mF, $\pm 4.0\%$

FREQ: 0 ~10kHz, $\pm 1.5\%$ (from clamp, or AC voltage)

Logic FREQ: 0 ~10MHz, $\pm 0.5\%$

Duty cycle: 10% ~90%, $\pm 3.0\%$

Audible continuity & diode test

Clamp size: 40mm (max.)

Battery: 9Vx1, 6F22

Dimensions & weight: 238x92x50mm, 340g approx.

Accessories: carrying case

REF: 032115A0000

✓ CE (EMC), □ UL, □ CE (LVD)