

UNI-T® UT630 SERIES

Digital AC Millivolt Meters

UT632



■ UT632

SPECIFICATIONS

Specifications	Range	Best Accuracy			
AC Voltage (V)	Frequency:	10Hz~200Hz	200Hz~500Hz	1kHz	500kHz~2MHz
	4mV	±(2%+0.1mV)	±(1%+0.1mV)	±(1%+15)	±(2%+0.1mV)
	40mV	±(5%+20)	±(3%+20)	±(0.5%+15)	±(5%+20)
	400mV	±(5%+20)	±(3%+20)	±(0.5%+15)	±(5%+20)
	4V	±(5%+20)	±(3%+20)	±(0.5%+15)	±(5%+20)
	40V	±(5%+20)	±(3%+20)	±(0.5%+15)	±(5%+20)
	400V	±(5%+20)	±(3%+20)	±(0.5%+15)	±(5%+20)
Features					
Display Count	4040				
Auto Range	√				
Bandwidth (Hz)	5Hz~2MHz				
Noise Voltage	≤18Digits				
Dual Channel	√				
USB Interface	√				
Input Impedance for DCV	R [^] ≥ 10MΩ		C [^] ≤ 47pF		

GENERAL CHARACTERISTICS

Power	220V±10% or 110V±10%(50Hz±4%,7VA)
LCD Size	157mm × 36mm
Product Color	Red and Grey
Product Net Weight	3.0Kg
Product Size	370mm × 222mm × 106mm
Standard Accessories	Test Leads, Power Cord, USB Interface Cable, PC Software CD
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	4 PCs
Standard Carton Measurement	690mm × 455mm × 320mm (0.10 CBM Per Standard Carton)
Standard Carton Gross Weight	21Kg