

Victor 70C Specifications		
Basic Function	Range	Basic accuracy
DC Voltage	400mV/4V/40V/400V/1000V	±(0.5%+4)
AC Voltage	400mV/4V/40V/400V/750V	±(0.8%+10)
DC Current	30mA/300mA/10A	±(1.5%+10)
AC Current	30mA/300mA/10A	±(1.5%+10)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(0.8%+4)
Capacitance	4nF/40nF/400nF/4uF/40uF/200uF	±(2.5%+20)
Frequency	100Hz/1000Hz/10kHz/100kHz/1MHz/30MHz	±(0.5%+10)

Special Features	
Diode	√
Continuity buzzer	√
Low battery indication	√
Data hold	√
Auto power off	√
Function protection	√
Relative value measurement	√
Shockproof protection	√
Temperature/ Humidity environment	Work environment : 0 ~ 40°C , Relative humidity < 80% Store environment : - 10 ~ 50°C , Relative humidity < 80%
Over range display	Display“OL”
Frequency/Duty cycle	1% ~ 99%
input impedance	10MΩ
sampling rate	3time/s
AC Frequency response	(40-400)Hz
Operation way	Keys spring Auto range
Max.Display	3999 (3 3/4 Auto polarity display or unit display)
LCD size	70×50mm
Battery	3V(1.5V×2)7#

General Characters	
Product color	Case: dark gray; Holster color: yellow
Product Net Weight	Approx: 320g (with battery)
Product Dimension	200×90×45mm