




UL/CUL Pending
 Registered Design No.: 0211977.6M004

UT33D Palm Size Digital Multimeters

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2000mV/20V/200V/500V	$\pm (0.5\%+2)$
AC Voltage	200V/500V	$\pm (1.2\%+10)$
DC Current	2000 μ A/20mA/200mA/10A	$\pm (1\%+2)$
Resistance	200 Ω /2000 Ω /20k Ω /200k Ω /20M Ω /200M Ω	$\pm (0.8\%+2)$
Special Functions		
Diode	✓	
Continuity Buzzer	✓	
Square Wave Output	✓	
Data Hold	✓	
Display Backlight	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	Around 10M Ω	
Max. Display	1999	

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	48 x 16mm
Product Colour	Red and Grey
Product Net Weight	Around 156g
Product Size	130 x 73.5 x 35mm
Standard Accessories	Test Lead, Battery, English Manual, Holster
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	60 pcs
Standard Carton Measurement	Around 486 x 345 x 310 mm (Around 0.052 CBM Per Standard Carton)
Standard Carton Gross Weight	Around 18kg

*Available at Extra Cost
 Specifications and other information are subject to change without further notice.