

Benchtop Scales PCE-TB 30C



**Professional benchtop scales up to 30 kg / resolution from 1 g / triple display /
Memory for up to 1,000 articles / monitoring of the number and weight of pieces /
Scanner, USB, PC, printer connection / optional OC switching contacts, 4-20 mA, 0-10 V**

The benchtop scale of the PCE-TB C series is a real professional aid for all counting tasks. The benchtop scales have an internal data memory for up to 1,000 items that can easily be stored e.g. they can be retrieved with a scanner. The article data that can be saved in the counting scale are: article description, scanner code, piece weight, permissible weight deviations MIN / MAX and the weight of the packaging (TARE). Using the counting scale with the possible information is very easy.

For this purpose, the data is created in spreadsheet-like software and transferred to the internal memory of the counting scale. Furthermore, the counting scales can transfer the counts carried out to a PC or optionally available USB memory stick. But even without the internal memory, the counting scale is a professional helper. If, for example, a barcode is not available in the data memory, the user is informed about this and still has the option to carry out further weighings / counts under the barcode and, if necessary, to save or transfer them to the PC. The inventory / counting carried out in this way saves a lot of reworking time and excludes transmission errors.

Despite the many keys, data maintenance on the professional counting scale is very easy. This can be done on the PC in the form of a table. Create a table e.g. in EXCEL, where the data: storage space, item description, barcode, piece weight, target weight, deviation tolerances (min. - max.) and tare weight are stored, these are saved as a CSV file. Perhaps this can also be done from your company's inventory management system. Then simply hand it over to the professional counting scales using the free software included in the scope of delivery. After the data has been successfully transferred, the articles can be accessed quickly and easily. This can be done using the direct selection buttons on the professional counting scales or with the help of an optionally available scanner.

Depending on the configuration of the professional counting scale, the data can be saved automatically as a TXT file directly in the PC or on a USB stick. The data can be composed of the user, article number, time, date and quantity. The data import of a TXT file into Excel is then very easy and enables a simple calculation of the count carried out. In the professional counting scales, unsaved products can also be counted and saved with the desired information, an article database maintenance is not necessary. This means that the professional counting scales can be used in most areas of application.

- ▶ internal memory for up to 1,000 articles
- ▶ article master processing with the help of PC
- ▶ triple display
- ▶ scanner connection (RS-232 Sub-D 9)
- ▶ RS-232 and USB interface
- ▶ summing function
- ▶ limit weight control
- ▶ memory for 10 tare weights

Subject to change

- ▶ optional: battery and scanner
- ▶ optional: LAN / Ethernet / network
- ▶ optional: USB data storage stick
- ▶ optional: 4-20 mA / 0-10 V analog output

Subject to change



Specifications

Model	Weighing range	Resolution	Measurement uncertainty
PCE-TB 30C	30 kg	1 g	± 3 g
Reference piece weight by weighing or entering			
Taring range	Multiple tare over the full weighing range		
Display	multi-display 16 mm digit height		
Memory	- for up to 5 users		
	- for 30 products via the quick selection buttons		
	- for a total of 1,000 product data records		
	- for 10 tare weights		
Product record	- location number		
	- article name		
	- barcode		
	- unit weight / target weight		
Data maintenance	- deviation tolerances / min. - max.		
	- tare weight		
	manually on the balance or		
	with the help of PC software and Excel		
Interfaces	RS-232 and USB		
	Scanner possible via RS-232 / Sub-D 9		
Settling time	Optional: 4-20 mA / 0-10 V / switching contacts		
Platform size	<3 s		
Calibration	300 x 210 mm (stainless steel)		
Power supply	external possible / freely selectable with M1 weights		
	230V / 50 Hz - 12V / 1.2A power supply		
Battery life	or 6V / 4.5Ah battery optional		
Operating temperature	ca. 90 hours / charging time approx. 12 hours		
Dimensions	-10...+35°C / 15% rH – 85% rH		
Weight	335 x 320 x 110 mm		
	ca. 3.5 kg		

More information

More product info



Similar products



Subject to change