

D.C. MILLI-OHM METER



GOM-801H



FEATURES

- * Measures from 20mΩ ~ 20kΩ in 7 Ranges
- * 1A High Test Current
- * High Resolution 10 μΩ
- * Hi/Lo Comparator Indicator and Buzz Alarm
- * 3 1/2 Digits 0.5" LED Display

GTL-108A Test Lead

For: GOM-801H/802 , GDM-8255A/8251A



The GOM-801H milliohm meter is the ideal device for quick and handy measurement for precise resistance of component and materials. The main display is equipped with 3 1/2 digits 0.5" LED in a distinctive red color. Measurable objects cover cable joints, earth bonds, switches, motors, transformers, generators, and many others. The test range is separated into seven levels between 20m and 20k , accessible from the front panel in a single press. An internal comparator provides a user settable Hi/Lo indication. The GOM-801H is the best way to go for an inexpensive, easy to use, yet reliable milliohm meter.

SPECIFICATIONS

TEST RANGE	
	20, 200m , 2, 20, 200 , 2k, 20k , 7 Ranges
TEST CURRENT (Test Voltage 02V)	
	20m /200m : 1A 2 : 0.1A 20 : 10mA 200 : 1mA 2k : 100μA 20k : 10μA
ACCURACY	
Measuring	20m ± (0.2% rdg + 6 digits) 200m ~ 20k ± (0.2% rdg + 4 digits)
Setting	± (0.2% + 6 digits)
RESOLUTION	
	0.01 , 0.1 , 1 , 10 , (≥ symbol) 100m , 1 , 10
COMPARATOR	
	HI, LO settable
DISPLAY	
	3 1/2 digits 0.5" LED display HI, GO, LO indicator
POWER SOURCE	
	AC 100V/120V/220V/230V±10% , 50/60Hz
DIMENSIONS & WEIGHT	
	230(W) x 95(H)x280(D)mm, Approx. 2 kg

ORDERING INFORMATION

GOM-801H High Precision Programmable DC Milli-Ohm Meter

ACCESSORIES :

User manual x 1 , Power cord x 1
Test Lead GTL-108A x 1