

TECHNICAL DATA

# Fluke TPS FLEX 24 Flexible Current Probe



## Specifications: Fluke TPS FLEX 24 Flexible Current Probe

General Specifications	
Measuring range selectable per software	2 A to 200 A
	10 A to 1000 A
Peak current for sinusoidal currents	480 A
	2700 A
Intrinsic error	1%
Frequency range	45 Hz to 3.0 kHz
Operating voltage	600 V CAT IV
Phase error	0.5°
Jaw opening	61 cm length
	2 m cable
Errors in % of measuring range at 23°C ± 2 K; 74°F ± 2 K, for 48 to 65 Hz Phase angle error at nominal current I <sub>max</sub> maximum current without time limit (for AC and DC shunts)	

## Ordering information



### **Fluke TPS FLEX 24**

Flexible Current Probe

---

**Fluke.** *Keeping your world up and running.*®

**Fluke Europe B.V.**  
P.O. Box 1186  
5602 BD Eindhoven  
The Netherlands  
[www.fluke.com/en](http://www.fluke.com/en)

**For more information call:**  
In Middle East/Africa  
+31 (0)40 267 5100

©2022 Fluke Corporation. All rights reserved.  
Data subject to alteration without notice.  
03/2022

**Modification of this document is not permitted  
without written permission from Fluke Corporation.**