



SPECIFICATIONS

Basic Functions	Range	Accuracy
		PE-M21
DC Voltage	200mV/2V/20V/200V/600V /400mV/4V/40V/ 400V/1000V	$\pm(0.7\%+3)$
AC Voltage	200mV/2V/20V/200V/600V 4V/40V/400V/750V	$\pm(1.2\%+3)$
DC Current	200 μ A/2mA/20mA/200mA/2A /10A/4000 μ A/400mA/10A	$\pm(2\%+8)$
AC Current	200 μ A/2mA/20mA/200mA/2A /10A/ 4000 μ A/400mA/10A	$\pm(3\%+8)$
Resistance	200 /2K /20K /200K /2M /20M /400 /4K /40K / 400K /4M /40M	$\pm(2\%+5)$
Capacitance	20nF/200nF/2 μ F/20 μ F/200 μ F /1000 μ F/4nF/40nF/400nF	$\pm(5\%+5)$

	/4 μ F/40 μ F/200 μ F				
Temperature	-20°C~1000°C -40°C~750°C		$\pm(1\%+3^\circ\text{C})$	$\pm(1\%+4^\circ\text{C})$	$\pm(1\%+4^\circ\text{C})$
	0°F~1800°F		$\pm(1\%+5^\circ\text{F})$	$\pm(1\%+7^\circ\text{F})$	
Frequency	10HZ~200KHZ				$\pm(0.1\%+1)$

Special Functions	PE-M21
Continuity Check	
Diode Test	
Transistor hFE Test	
AutoRange	
Misplug Alarm	
No Contact AC Voltage Detector	
Back Light	
MAX Value Measurement	
Relative Measurement	
MAX/MIN Value Measurement	
Data Hold	
Auto Power Off	
Low Power Indication	
Max. Display	3999