PE-M30S Counts Intelligent Multimeter



This multimeters are rugged and reliable, hand-held or system instruments for maintenance, initial start-up, training and R&D in industry, for government authorities, in the test lab, in manufacturing and quality assurance, as well as at universities.

Key Feature:

22000 counts measurement ACV and DCV measurements reach up to 1000V. DC measurement accuracy reaches up to 0.05%. 0.01 resistance resolution and 10µV voltage resolution. Linear frequency measurement, logic frequency/duty ratio measurement. Capacitance measurement from 0.001nf to 220mF. AC true RMS measurement. (only for model) Temperature Measurement. Maximum value / minimum value measurement, Relative measurement, PEAKmax/min measurement. 46-segment analog bar display. Automatic shutdown/continuous working mode selection. Back light control. PC-LINK: USB infrared interface. Display, record and graphics software of computer. Overload protection.

SOLID CONVERTER

www.behrooz-tools.com

Sound alarm for misplug.

Secondary plasticizing meter shell, with insulating performance reaching 1000V CAT II

SPECIFICATIONS

Basic Functions	Range	Accuracy
DC Voltage	220mV	±0.1%
	2.2V/22V/220V/1000V	±0.2%
AC Voltage	220mV	±0.5%
	2.2V/22V/220V/1000V	±0.8%
DC Current	220µA/2200µA/22mA/220mA	±0.3%
	10A	±0.8%
AC Current	220µA/2200µA/22mA/220mA	±1.0%
	10A	±1.5%
Resistance	220	±0.5%
	2.2K /22K	±0.8%
	220K /2.2M	±1.0%
	22M	±1.2%
	220M	±1.5%
Capacitance	22nF/220nF/2.2µF	±1.0%
	22µF/220µF	±1.5%
	2.2mF	±2.5%
	22mF	±3.0%
	220mF	±5.0%
Temperature	-55°C~50°C	±3.0%
	50°C~400°C	±1.0%
	400°C~1000°C	±2.5%
Logic Frequency	2Hz~10MHz	±0.05%
Linear Frequency	2Hz~200KHz	±0.05%
Duty Cycle	5%~94.9%	±2.0%

Solid Converter PDF

www.behrooz-tools.com

2

To remove this message, purchase the

product at www.SolidDocuments.com

Special Functions	PE-N	130S
True RMS Measurement		
Diode Test		
Continuity Check		
Auto Power Off		
Low Power Indication		
Back Light		
Data Hold		
Peak Hold		
Relative Measurement		
MAX/MIN Value Measurement		
Misplug Alarm		
Max. Display	22000	

GENERAL CHARACTERISTICS

Power Supply	1.5V battery (AAA)*6
LCD Size	64x42
Product Color	Grey+yellow
Product Size	205x97x45
Standard Accessories	Test Lead、User's Manual、USB interface cable、Software、Battery
Standard Individual Packing	Gift Box

Solid Converter PDF

www.behrooz-tools.com