

UT61E

CE

Modern Digital Multimeters**SPECIFICATIONS**

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2.2V/22V/220V/1000V	±(0.1%+2)
AC Voltage	200mV/2.2V/22V/220V/150V	±(0.8%+10)
AC Current	200mA/2000mA/20mA/200mA/2.2A/10A	±(0.8%+10)
DC Current	200mA/2000mA/20mA/200mA/2.2A/10A	±(0.8%+10)
Resistance	200W/2.2KW/20W/200W/2.2MW/20MW/200MW	±(0.8%+10)
Capacitance	20nF/200nF/2.2µF/22µF/220µF/2.2mF/20mF/200mF	±(3.0%+5)
Frequency	10Hz-200MHz	±(0.01%+5)
Frequency Response		45Hz-10kHz
Duty Cycle	0.1% - 99.9%	✓
Special Functions		
Auto/Manual Ranging		✓
Diode		✓
RMS		✓
Continuity Buzzer		✓
Data Hold		✓
Peak Value		✓
Display Backlight		✓
REL		✓
Sleep Mode	Around 15 Minutes	✓
Analogue Bar Graph		45
R5232		✓
Input Protection		✓
Input Impedance for DC Voltage Measurement	Around 10MΩ	✓
Low Battery Display	≈1.5V	✓
Max Display		20000

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	65 x 43mm
Product Colour	Red and Grey
Product Net Weight	370g
Product Size	180 x 87 x 47mm
Standard Accessories	Battery, Test Lead, English Manual, Multi-Purpose Socket, RS232 Interface Cable, Software
Optional Accessories*	USB Interface Cable
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	20pcs
Standard Carton Measurement	465 x 335 x 349mm (0.054CBM Per Standard Carton)
Standard Carton Gross Weight	12kg