

UT50A



[Enlarge](#)



Registered Design No.: 0211977.6M003

[Download Manual](#)

Modern Digital Multimeters

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	± (0.5%+1)
AC Voltage	200mV/2V/20V/200V/750V	± (0.8%+3)
DC Current	20mA/2mA/200mA/20A	± (0.8%+1)
AC Current	200mA/2mA/200mA/20A	± (1%+3)
Resistance	200W/2kW/20kW/200kW/2MW/20MW/200MW	± (0.8%+1)
Capacitance	2nF/20nF/2mF/100mF	± (4%+3)
Temperature (°C)	-40°C ~ 1000°C	± (1%+3)
Temperature (°F)	-40°F ~ 1832°F	± (1%+4)
Special Functions		
Diode		✓
Continuity Buzzer		✓
Data Hold		✓
Display Backlight	Auto Sensor	✓
Full Icon Display		✓
Sleep Mode		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around 10MW	✓
Max. Display	1999	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	59 x 25mm
Product Colour	Red and Grey
Product Net Weight	275g
Product Size	165 x 80 x 38.3mm
Standard Accessories	Test Lead, Battery, English Manual, Test Clip
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40pcs
Standard Carton Measurement	598 x 418 x 340mm (Around 0.085 CBM Per Standard Carton)
Standard Carton Gross Weight	21kg

Specifications and other information are subject to change without further notice.

[Back to main menu](#)