



EN:61010-1

EN:61326-1



■ UT90A



■ UT90B

SPECIFICATIONS



Specifications	Range	Best Accuracy	
		UT90A	UT90B
Model			
DC Voltage (V)	200mV/2V/20V/200V/1000V	±(0.5%+2)	±(0.5%+2)
AC Voltage (V)	2V/20V/200V/750V	±(0.8%+5)	±(0.8%+5)
DC Current (A)	200µA/2mA/20mA/200mA/10A	±(0.8%+2)	±(1%+2)
AC Current (A)	200µA/2mA/20mA/200mA/10A	±(1%+5)	±(1.2%+5)
Resistance (Ω)	200Ω/2KΩ/20KΩ/200KΩ/2MΩ/20MΩ	±(0.8%+3)	±(0.8%+3)
Features			
Display Count		1999	1999
Manual Range		✓	✓
Solar Power			✓
Battery Test	1.5V/9V	✓	
Diode		✓	✓
Continuity Buzzer		✓	✓
Low Battery Indication		✓	✓
Data Hold		✓	
Full Icon Display		✓	✓
Input Protection		✓	✓
Input Impedance for DCV	Around 10MΩ	✓	✓
Low Impedance Selection			✓

GENERAL CHARACTERISTICS

Power	UT90A-9V Battery (6F22) UT90B-Charging at AC 230V or AC/DC12-36V or Solar Power
LCD Size	UT90A-60mm × 54mm ,UT90B-60mm × 26mm
Product Color	Red and Grey
Product Net Weight	UT90A-351g (Including Holster) ,UT90B-340g (Including Holster)
Product Size	179mm × 88mm × 39mm
Standard Accessories	UT90A Battery,Holster, Test Lead, UT90B-Holster, Test Lead
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	598mm × 418mm × 340mm (0.085 CBM Per Standard Carton)
Standard Carton Gross Weight	23 Kg