

UTD2025C**Digital Storage Oscilloscope****SPECIFICATIONS**
[Enlarge](#)
[Download Manual](#)
[Download Software](#)

| Feature | UTD2025C |
|---------------------------------|---|
| Bandwidth | 25 MHz |
| Rise Time | ≤14 ns |
| Sample Range | 250MS/s |
| Vertical Sensitivity | 2mV ~ 10V/div |
| Record Length (Max) | 2 x 512k |
| Sample Rate | Real time 250MS/s |
| Scan Time Base | 20ns ~ 50s/div |
| Trigger Type | Edge, Pulse, Video and Alternate |
| Automatic Waveform Measurements | 28 |
| Ports | Standard: USB Device, USB Host, PASS/FAIL. Optional: LAN |
| Mathematics | Add, Subtract, Multiply, Divide, FFT |
| Applications | College Education, R&D, Electronic product assemble line, Industrial Control etc. |
| Display | 64k, Full colour LCD, 320 x 240 |

GENERAL CHARACTERISTICS

| | |
|------------------------------|---|
| Power | 100 - 240VACRMS, 45Hz - 440Hz, CAT II |
| LCD Size | Diagonal 145mm (5.7 inches) |
| Product Color | Red and Grey |
| Product Net Weight | 2.5kg (Excluding packaging) |
| Product Size | 320mm x 150mm x 130mm |
| Standard Accessories | Probe x 2 (1x, 10x switchable), Power Cord and English Manual |
| Standard Individual Packing | Gift Box |
| Standard Quantity Per Carton | 2 pcs |
| Standard Carton Measurement | 445 x 410 x 270mm (0.055 CBM Per Export Carton) |
| Standard Carton Gross Weight | 9.2kg |

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD2042C**Digital Storage Oscilloscope****SPECIFICATIONS**
[Enlarge](#)
[Download Manual](#)
[Download Software](#)

| Feature | UTD2042C |
|---------------------------------|---|
| Bandwidth | 40 MHz |
| Rise Time | ≤8.7 ns |
| Sample Range | 500MS/s |
| Vertical Sensitivity | 2mV ~ 5V/div |
| Record Length (Max) | 2 x 512k |
| Sample Rate | Real time 500MS/s, Equivalent: 25GS/s |
| Scan Time Base | 5ns ~ 50s/div |
| Trigger Type | Edge, Pulse, Video and Alternate |
| Automatic Waveform Measurements | 28 |
| Ports | Standard: USB Device, USB Host, RS232. Optional: LAN |
| Mathematics | Add, Subtract, Multiply, Divide, FFT |
| Applications | College Education, R&D, Electronic product assemble line, Industrial Control etc. |
| Display | 64k, Full colour LCD, 320 x 240 |

GENERAL CHARACTERISTICS

| | |
|------------------------------|---|
| Power | 100 - 240VACRMS, 45Hz - 440Hz, CAT II |
| LCD Size | Diagonal 145mm (5.7 inches) |
| Product Color | Red and Grey |
| Product Net Weight | 2.5kg (Excluding packaging) |
| Product Size | 320mm x 150mm x 130mm |
| Standard Accessories | Probe x 2 (1x, 10x switchable), Power Cord and English Manual |
| Standard Individual Packing | Gift Box |
| Standard Quantity Per Carton | 2 pcs |
| Standard Carton Measurement | 445 x 410 x 270mm (0.055 CBM Per Export Carton) |
| Standard Carton Gross Weight | 9.2kg |

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD2062C
[Enlarge](#)
[Download Manual](#)
[Download Software](#)
Digital Storage Oscilloscope**SPECIFICATIONS**

| Feature | UTD2062C |
|---------------------------------|---|
| Bandwidth | 60 MHz |
| Rise Time | ≤5.8 ns |
| Sample Range | 500MS/s |
| Vertical Sensitivity | 2mV ~ 5V/div |
| Record Length (Max) | 2 x 512k |
| Sample Rate | Real time 500MS/s, Equivalent: 25GS/s |
| Scan Time Base | 5ns ~ 50s/div |
| Trigger Type | Edge, Pulse, Video and Alternate |
| Automatic Waveform Measurements | 28 |
| Ports | Standard: USB Device, USB Host, RS232. Optional: LAN |
| Mathematics | Add, Subtract, Multiply, Divide, FFT |
| Applications | College Education, R&D, Electronic product assemble line, Industrial Control etc. |
| Display | 64k, Full colour LCD, 320 x 240 |

GENERAL CHARACTERISTICS

| | |
|------------------------------|---|
| Power | 100 - 240VACRMS, 45Hz - 440Hz, CAT II |
| LCD Size | Diagonal 145mm (5.7 inches) |
| Product Color | Red and Grey |
| Product Net Weight | 2.5kg (Excluding packaging) |
| Product Size | 320mm x 150mm x 130mm |
| Standard Accessories | Probe x 2 (1x, 10x switchable), Power Cord and English Manual |
| Standard Individual Packing | Gift Box |
| Standard Quantity Per Carton | 2 pcs |
| Standard Carton Measurement | 445 x 410 x 270mm (0.055 CBM Per Export Carton) |
| Standard Carton Gross Weight | 9.2kg |

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD2082C
[Enlarge](#)
[Download Manual](#)
[Download Software](#)
Digital Storage Oscilloscope**SPECIFICATIONS**

| Feature | UTD2082C |
|---------------------------------|---|
| Bandwidth | 80 MHz |
| Rise Time | ≤4.5 ns |
| Sample Range | 500MS/s |
| Vertical Sensitivity | 2mV ~ 5V/div |
| Record Length (Max) | 2 x 512k |
| Sample Rate | Real time 500MS/s, Equivalent: 25GS/s |
| Scan Time Base | 5ns ~ 50s/div |
| Trigger Type | Edge, Pulse, Video and Alternate |
| Automatic Waveform Measurements | 28 |
| Ports | Standard: USB Device, USB Host, RS232. Optional: LAN |
| Mathematics | Add, Subtract, Multiply, Divide, FFT |
| Applications | College Education, R&D, Electronic product assemble line, Industrial Control etc. |
| Display | 64k, Full colour LCD, 320 x 240 |

GENERAL CHARACTERISTICS

| | |
|------------------------------|---|
| Power | 100 - 240VACRMS, 45Hz - 440Hz, CAT II |
| LCD Size | Diagonal 145mm (5.7 inches) |
| Product Color | Red and Grey |
| Product Net Weight | 2.5kg (Excluding packaging) |
| Product Size | 320mm x 150mm x 130mm |
| Standard Accessories | Probe x 2 (1x, 10x switchable), Power Cord and English Manual |
| Standard Individual Packing | Gift Box |
| Standard Quantity Per Carton | 2 pcs |
| Standard Carton Measurement | 445 x 410 x 270mm (0.055 CBM Per Export Carton) |
| Standard Carton Gross Weight | 9.2kg |

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD2102C**Digital Storage Oscilloscope****SPECIFICATIONS**
[Enlarge](#)
[Download Manual](#)
[Download Software](#)

| Feature | UTD2102C |
|---------------------------------|---|
| Bandwidth | 100 MHz |
| Rise Time | ≤ 3.5 ns |
| Sample Range | 500MS/s |
| Vertical Sensitivity | 2mV ~ 5V/div |
| Record Length (Max) | 2 x 512k |
| Sample Rate | Real time 500MS/s, Equivalent: 25GS/s |
| Scan Time Base | 5ns ~ 50s/div |
| Trigger Type | Edge, Pulse, Video and Alternate |
| Automatic Waveform Measurements | 28 |
| Ports | Standard: USB Device, USB Host, RS232. Optional: LAN |
| Mathematics | Add, Subtract, Multiply, Divide, FFT |
| Applications | College Education, R&D, Electronic product assemble line, Industrial Control etc. |
| Display | 64k, Full colour LCD, 320 x 240 |

GENERAL CHARACTERISTICS

| | |
|------------------------------|---|
| Power | 100 - 240VACRMS, 45Hz - 440Hz, CAT II |
| LCD Size | Diagonal 145mm (5.7 inches) |
| Product Color | Red and Grey |
| Product Net Weight | 2.5kg (Excluding packaging) |
| Product Size | 320mm x 150mm x 130mm |
| Standard Accessories | Probe x 2 (1x, 10x switchable), Power Cord and English Manual |
| Standard Individual Packing | Gift Box |
| Standard Quantity Per Carton | 2 pcs |
| Standard Carton Measurement | 445 x 410 x 270mm (0.055 CBM Per Export Carton) |
| Standard Carton Gross Weight | 9.2kg |

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD2152C**Digital Storage Oscilloscope****SPECIFICATIONS**
[Enlarge](#)
[Download Manual](#)
[Download Software](#)

| Feature | UTD2152C |
|---------------------------------|---|
| Bandwidth | 150 MHz |
| Rise Time | ≤2.3 ns |
| Sample Range | 500MS/s |
| Vertical Sensitivity | 2mV ~ 5V/div |
| Record Length (Max) | 2 x 512k |
| Sample Rate | Real time 500MS/s, Equivalent: 25GS/s |
| Scan Time Base | 2ns ~ 50s/div |
| Trigger Type | Edge, Pulse, Video and Alternate |
| Automatic Waveform Measurements | 28 |
| Ports | Standard: USB Device, USB Host, RS232. Optional: LAN |
| Mathematics | Add, Subtract, Multiply, Divide, FFT |
| Applications | College Education, R&D, Electronic product assemble line, Industrial Control etc. |
| Display | 64k, Full colour LCD, 320 x 240 |

GENERAL CHARACTERISTICS

| | |
|------------------------------|---|
| Power | 100 - 240VACRMS, 45Hz - 440Hz, CAT II |
| LCD Size | Diagonal 145mm (5.7 inches) |
| Product Color | Red and Grey |
| Product Net Weight | 2.5kg (Excluding packaging) |
| Product Size | 320mm x 150mm x 130mm |
| Standard Accessories | Probe x 2 (1x, 10x switchable), Power Cord and English Manual |
| Standard Individual Packing | Gift Box |
| Standard Quantity Per Carton | 2 pcs |
| Standard Carton Measurement | 445 x 410 x 270mm (0.055 CBM Per Export Carton) |
| Standard Carton Gross Weight | 9.2kg |

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD2202C
[Enlarge](#)
[Download Manual](#)
[Download Software](#)
Digital Storage Oscilloscope**SPECIFICATIONS**

| Feature | UTD2202C |
|---------------------------------|---|
| Bandwidth | 200 MHz |
| Rise Time | ≤ 1.8 ns |
| Sample Range | 500MS/s |
| Vertical Sensitivity | 2mV ~ 5V/div |
| Record Length (Max) | 2 x 512k |
| Sample Rate | Real time 500MS/s, Equivalent: 25GS/s |
| Scan Time Base | 2ns ~ 50s/div |
| Trigger Type | Edge, Pulse, Video and Alternate |
| Automatic Waveform Measurements | 28 |
| Ports | Standard: USB Device, USB Host, RS232. Optional: LAN |
| Mathematics | Add, Subtract, Multiply, Divide, FFT |
| Applications | College Education, R&D, Electronic product assemble line, Industrial Control etc. |
| Display | 64k, Full colour LCD, 320 x 240 |

GENERAL CHARACTERISTICS

| | |
|------------------------------|---|
| Power | 100 - 240VACRMS, 45Hz - 440Hz, CAT II |
| LCD Size | Diagonal 145mm (5.7 inches) |
| Product Color | Red and Grey |
| Product Net Weight | 2.5kg (Excluding packaging) |
| Product Size | 320mm x 150mm x 130mm |
| Standard Accessories | Probe x 2 (1x, 10x switchable), Power Cord and English Manual |
| Standard Individual Packing | Gift Box |
| Standard Quantity Per Carton | 2 pcs |
| Standard Carton Measurement | 445 x 410 x 270mm (0.055 CBM Per Export Carton) |
| Standard Carton Gross Weight | 9.2kg |

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)