



**SPECIFICATIONS**

Specifications	UTD2042CM	UTD2062CM
Channels		2
Bandwidth	40MHz	60MHz
Sample Rate		1GS/s
Rise Time	≤8.7ns	≤5.8ns
Memory Depth		16Mpts
Waveform Acquisition Rate		≥150000wfms/s
Vertical Sensitivity		2mV/div~10V/div
Time-Based Range		2ns/div~50s/div
Storage		Setup, Wave, Bitmap, CSV
Trigger Modes		Edge, Pluse, Video, Slope, Alternate
Interface		USB Device, USB Host, Pass/Fail

**GENERAL CHARACTERISTICS**

Power	100-240VAC, 40-440Hz
Display	7 Inches 64K Color TFT LCD, (800×480)
Product Color	Red and Gray
Product Net Weight	2.9Kg
Product Size	330mm × 155mm × 130mm
Standard Accessories	Probex2(1×,10× switchable),Power Cord ,USB Cable,PC Software CD
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	2 PCs
Standard Carton Measurement	450mm × 420mm × 280mm (0.053 CBM Per Standard Carton)
Standard Carton Gross Weight	10Kg
Optional Accessories	LAN Communication Port, RS-232 Cable