

UTD3025B

Digital Storage Oscilloscope

SPECIFICATIONS


[Enlarge](#)
[Download Manual](#)
[Download Software](#)

Feature	UTD3025B
Bandwidth	25 MHz
Rise Time	≤14 ns
Sample Range	250MS/s
Vertical Sensitivity	2mV ~ 10V/div
Record Length (Max)	2 x 512k
Sample Rate	Real time 250MS/s
Scan Time Base	20ns ~ 50s/div
Trigger Type	Edge, Pulse, Video, Alter
Automatic Waveform Measurements	28
Ports	Standard: USB Device, USB Host, PASS/FAIL. Optional: LAN
Mathematics	Add, Subtract, Multiply, Divide, FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Display	Monochrome LCD, 320 x 240

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey
Product Net Weight	4.9kg (Excluding packaging)
Product Size	320mm x 150mm x 292mm
Standard Accessories	Probe x 2 (1x, 10x switchable), Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	430 x 380 x 540mm (0.092 CBM Per Export Carton)
Standard Carton Gross Weight	14.8kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD3062B

Digital Storage Oscilloscope

SPECIFICATIONS


[Enlarge](#)
[Download Manual](#)
[Download Software](#)

Feature	UTD3062B
Bandwidth	60 MHz
Rise Time	≤5.8 ns
Sample Range	500MS/s
Vertical Sensitivity	2mV ~ 5V/div
Record Length (Max)	2 x 512k
Sample Rate	Real time, 500MS/s, Equivalent: 25GS/s
Scan Time Base	5ns ~ 50s/div
Trigger Type	Edge, Pulse, Video, Alter
Automatic Waveform Measurements	28
Ports	Standard: USB Device, USB Host, RS232, Optional: LAN
Mathematics	Add, Subtract, Multiply, Divide, FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Display	Monochrome LCD, 320 x 240

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey, White and Grey
Product Net Weight	4.9kg (Excluding packaging)
Product Size	320mm x 150mm x 292mm
Standard Accessories	Probe x 2 (1x, 10x switchable), Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	430 x 380 x 540mm (0.092 CBM Per Export Carton)
Standard Carton Gross Weight	14.8kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD3102B

Digital Storage Oscilloscope

SPECIFICATIONS


[Enlarge](#)
[Download Manual](#)
[Download Software](#)

Feature	UTD3102B
Bandwidth	100 MHz
Rise Time	≤3.5 ns
Sample Range	500MS/s
Vertical Sensitivity	2mV ~ 5V/div
Record Length (Max)	2 x 512k
Sample Rate	Real time, 500MS/s, Equivalent: 25GS/s
Scan Time Base	5ns ~ 50s/div
Trigger Type	Edge, Pulse, Video and Alternate
Automatic Waveform Measurements	28
Ports	Standard: USB Device, USB Host, RS232, Optional: LAN & GPIB
Mathematics	Add, Subtract, Multiply, Divide, FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Display	Monochrome LCD, 320 x 240

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey, White and Grey
Product Net Weight	4.9kg (Excluding packaging)
Product Size	320mm x 150mm x 292mm
Standard Accessories	Probe x 2 (1x, 10x switchable), Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	430 x 380 x 540mm (0.092 CBM Per Export Carton)
Standard Carton Gross Weight	14.8kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD3202B

Digital Storage Oscilloscope

SPECIFICATIONS


[Enlarge](#)
[Download Manual](#)
[Download Software](#)

Feature	UTD3202B
Bandwidth	200 MHz
Rise Time	≤1.8 ns
Sample Range	500MS/s
Vertical Sensitivity	2mV ~ 5V/div
Record Length (Max)	2 x 512k
Sample Rate	Real time, 500MS/s, Equivalent: 25GS/s
Scan Time Base	2ns ~ 50s/div
Trigger Type	Edge, Pulse, Video and Alternate
Automatic Waveform Measurements	28
Ports	Standard: USB Device, USB Host, RS232, Optional: LAN & GPIB
Mathematics	Add, Subtract, Multiply, Divide, FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Display	Monochrome LCD, 320 x 240

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey, White and Grey
Product Net Weight	4.9kg (Excluding packaging)
Product Size	320mm x 150mm x 292mm
Standard Accessories	Probe x 2 (1x, 10x switchable), Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	430 x 380 x 540mm (0.092 CBM Per Export Carton)
Standard Carton Gross Weight	14.8kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD3202C


[Enlarge](#)
[Download Manual](#)
[Download Software](#)

Digital Storage Oscilloscope

SPECIFICATIONS

Feature	UTD3202C
Bandwidth	200 MHz
Rise Time	≤1.8 ns
Sample Range	500MS/s
Vertical Sensitivity	2mV ~ 5V/div
Record Length (Max)	2 x 512k
Sample Rate	Real time 500MS/s, Equivalent: 25GS/s
Scan Time Base	2ns ~ 50s/div
Trigger Type	Edge, Pulse, Video and Alternate
Automatic Waveform Measurements	28
Ports	Standard: USB Device, USB Host, RS232. Optional: LAN
Mathematics	Add, Subtract, Multiply, Divide, FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Display	64k, Full colour LCD, 320 x 240

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey
Product Net Weight	4.9kg (Excluding packaging)
Product Size	320mm x 150mm x 292mm
Standard Accessories	Probe x 2 (1x, 10x switchable), Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	430 x 380 x 540mm (0.092 CBM Per Export Carton)
Standard Carton Gross Weight	14.8kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD3025C

Digital Storage Oscilloscope

SPECIFICATIONS


[Enlarge](#)
[Download Manual](#)
[Download Software](#)

Feature	UTD3025C
Bandwidth	25 MHz
Rise Time	≤14 ns
Sample Range	250MS/s
Vertical Sensitivity	2mV ~ 10V/div
Record Length (Max)	2 x 512k
Sample Rate	Real time 250MS/s
Scan Time Base	20ns ~ 50s/div
Trigger Type	Edge, Pulse, Video and Alternate
Automatic Waveform Measurements	28
Ports	Standard: USB Device, USB Host, PASS/FAIL. Optional: LAN
Mathematics	Add, Subtract, Multiply, Divide, FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Display	64k, Full colour LCD, 320 x 240

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey
Product Net Weight	4.9kg (Excluding packaging)
Product Size	320mm x 150mm x 292mm
Standard Accessories	Probe x 2 (1x, 10x switchable), Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	430 x 380 x 540mm (0.092 CBM Per Export Carton)
Standard Carton Gross Weight	14.8kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD3042C

Digital Storage Oscilloscope

SPECIFICATIONS


[Enlarge](#)
[Download Manual](#)
[Download Software](#)

Feature	UTD3042C
Bandwidth	40 MHz
Rise Time	≤8.7 ns
Sample Range	500MS/s
Vertical Sensitivity	2mV ~ 5V/div
Record Length (Max)	2 x 512k
Sample Rate	Real time 500MS/s, Equivalent: 25GS/s
Scan Time Base	10ns ~ 50s/div
Trigger Type	Edge, Pulse, Video, Alter
Automatic Waveform Measurements	28
Ports	Standard: USB Device, USB Host, RS232. Optional: LAN
Mathematics	Add, Subtract, Multiply, Divide, FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Display	64k, Full colour LCD, 320 x 240

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey
Product Net Weight	4.9kg (Excluding packaging)
Product Size	320mm x 150mm x 292mm
Standard Accessories	Probe x 2 (1x, 10x switchable), Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	430 x 380 x 540mm (0.092 CBM Per Export Carton)
Standard Carton Gross Weight	14.8kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD3062C

Digital Storage Oscilloscope

SPECIFICATIONS


[Enlarge](#)
[Download Manual](#)
[Download Software](#)

Feature	UTD3062C
Bandwidth	60 MHz
Rise Time	≤5.8 ns
Sample Range	500MS/s
Vertical Sensitivity	2mV ~ 5V/div
Record Length (Max)	2 x 512k
Sample Rate	Real time 500MS/s, Equivalent: 25GS/s
Scan Time Base	5ns ~ 50s/div
Trigger Type	Edge, Pulse, Video, Alter
Automatic Waveform Measurements	28
Ports	Standard: USB Device, USB Host, RS232. Optional: LAN
Mathematics	Add, Subtract, Multiply, Divide, FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Display	64k, Full colour LCD, 320 x 240

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey
Product Net Weight	4.9kg (Excluding packaging)
Product Size	320mm x 150mm x 292mm
Standard Accessories	Probe x 2 (1x, 10x switchable), Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	430 x 380 x 540mm (0.092 CBM Per Export Carton)
Standard Carton Gross Weight	14.8kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD3082C

Digital Storage Oscilloscope

SPECIFICATIONS


[Enlarge](#)
[Download Manual](#)
[Download Software](#)

Feature	UTD3082C
Bandwidth	80 MHz
Rise Time	≤4.5 ns
Sample Range	500MS/s
Vertical Sensitivity	2mV ~ 5V/div
Record Length (Max)	2 x 512k
Sample Rate	Real time 500MS/s, Equivalent: 25GS/s
Scan Time Base	5ns ~ 50s/div
Trigger Type	Edge, Pulse, Video and Alternate
Automatic Waveform Measurements	28
Ports	Standard: USB Device, USB Host, RS232. Optional: LAN
Mathematics	Add, Subtract, Multiply, Divide, FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Display	64k, Full colour LCD, 320 x 240

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey
Product Net Weight	4.9kg (Excluding packaging)
Product Size	320mm x 150mm x 292mm
Standard Accessories	Probe x 2 (1x, 10x switchable), Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	430 x 380 x 540mm (0.092 CBM Per Export Carton)
Standard Carton Gross Weight	14.8kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD3102C

Digital Storage Oscilloscope

SPECIFICATIONS


[Enlarge](#)
[Download Manual](#)
[Download Software](#)

Feature	UTD3102C
Bandwidth	100 MHz
Rise Time	≤3.5 ns
Sample Range	500MS/s
Vertical Sensitivity	2mV ~ 5V/div
Record Length (Max)	2 x 512k
Sample Rate	Real time 500MS/s, Equivalent: 25GS/s
Scan Time Base	5ns ~ 50s/div
Trigger Type	Edge, Pulse, Video and Alternate
Automatic Waveform Measurements	28
Ports	Standard: USB Device, USB Host, RS232. Optional: LAN
Mathematics	Add, Subtract, Multiply, Divide, FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Display	64k, Full colour LCD, 320 x 240

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey
Product Net Weight	4.9kg (Excluding packaging)
Product Size	320mm x 150mm x 292mm
Standard Accessories	Probe x 2 (1x, 10x switchable), Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	430 x 380 x 540mm (0.092 CBM Per Export Carton)
Standard Carton Gross Weight	14.8kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD3152C

Digital Storage Oscilloscope


[Enlarge](#)
[Download Manual](#)
[Download Software](#)

SPECIFICATIONS

Feature	UTD3152C
Bandwidth	150 MHz
Rise Time	≤2.3 ns
Sample Range	500MS/s
Vertical Sensitivity	2mV ~ 5V/div
Record Length (Max)	2 x 512k
Sample Rate	Real time 500MS/s, Equivalent: 25GS/s
Scan Time Base	2ns ~ 50s/div
Trigger Type	Edge, Pulse, Video and Alternate
Automatic Waveform Measurements	28
Ports	Standard: USB Device, USB Host, RS232. Optional: LAN
Mathematics	Add, Subtract, Multiply, Divide, FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Display	64k, Full colour LCD, 320 x 240

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey
Product Net Weight	4.9kg (Excluding packaging)
Product Size	320mm x 150mm x 292mm
Standard Accessories	Probe x 2 (1x, 10x switchable), Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	430 x 380 x 540mm (0.092 CBM Per Export Carton)
Standard Carton Gross Weight	14.8kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)