

UTD4042C**Digital Storage Oscilloscope****SPECIFICATIONS**
[Enlarge](#)

Feature	UTD4042C
Bandwidth	40 MHz
Rise Time	≤8.7 ns
Sample Range	2GS/s
Vertical Sensitivity	1mV ~ 10V/div
Record Length (Max)	1024k
Sample Rate	2GS/s
Scan Time Base	5ns ~ 50s/div
Trigger Type	Edge, Pulse, Video, Slope and LA
Automatic Waveform Measurements	27
Ports	Standard: USB Device, USB Host; PASS/FAIL, LA interface, Multimeter interface, LAN and GPIB
Mathematics	Add, Subtract, Multiply, FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Display	Digital Multimeter and Logic Analyzer

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey
Product Net Weight	3.8kg (Excluding packaging)
Product Size	330mm x 165mm x 165mm
Standard Accessories	Probe x 2 (1x, 10x switchable), Logic Analyzer Probe UT-P06, Current-to-Voltage Convertor module, (UT-M03, UT-M04) Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	540 x 425 x 325mm (0.063 CBM Per Export Carton)
Standard Carton Gross Weight	Around 13.7kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD4062C
[Enlarge](#)
Digital Storage Oscilloscope**SPECIFICATIONS**

Feature	UTD4062C
Bandwidth	60 MHz
Rise Time	≤5.8 ns
Sample Range	2GS/s
Vertical Sensitivity	1mV ~ 10V/div
Record Length (Max)	1024k
Sample Rate	2GS/s
Scan Time Base	5ns ~ 50s/div
Trigger Type	Edge, Pulse, Video, Slope and LA
Automatic Waveform Measurements	27
Ports	Standard: USB Device, USB Host; PASS/FAIL, LA interface, Multimeter interface, LAN and GPIB
Mathematics	Add, Subtract, Multiply, FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Display	Digital Multimeter and Logic Analyzer

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey
Product Net Weight	3.8kg (Excluding packaging)
Product Size	330mm x 165mm x 165mm
Standard Accessories	Probe x 2 (1x, 10x switchable), Logic Analyzer Probe UT-P06, Current-to-Voltage Converter module, (UT-M03, UT-M04) Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	540 x 425 x 325mm (0.063 CBM Per Export Carton)
Standard Carton Gross Weight	Around 13.7kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD4082C**Digital Storage Oscilloscope**
[Enlarge](#)
SPECIFICATIONS

Feature	UTD4082C
Bandwidth	80 MHz
Rise Time	≤4.3 ns
Sample Range	2GS/s
Vertical Sensitivity	1mV ~ 10V/div
Record Length (Max)	1024k
Sample Rate	2GS/s
Scan Time Base	5ns ~ 50s/div
Trigger Type	Edge, Pulse, Video, Slope and LA
Automatic Waveform Measurements	27
Ports	Standard: USB Device, USB Host; PASS/FAIL, LA interface, Multimeter interface, LAN and GPIB
Mathematics	Add, Subtract, Multiply, FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Display	Digital Multimeter and Logic Analyzer

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey
Product Net Weight	3.8kg (Excluding packaging)
Product Size	330mm x 165mm x 165mm
Standard Accessories	Probe x 2 (1x, 10x switchable), Logic Analyzer Probe UT-P06, Current-to-Voltage Converter module, (UT-M03, UT-M04) Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	540 x 425 x 325mm (0.063 CBM Per Export Carton)
Standard Carton Gross Weight	Around 13.7kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD4102C**Digital Storage Oscilloscope****SPECIFICATIONS**
[Enlarge](#)

Feature	UTD4102C
Bandwidth	100 MHz
Rise Time	≤3.5 ns
Sample Range	2GS/s
Vertical Sensitivity	1mV ~ 10V/div
Record Length (Max)	1024k
Sample Rate	2GS/s
Scan Time Base	5ns ~ 50s/div
Trigger Type	Edge, Pulse, Video, Slope and LA
Automatic Waveform Measurements	27
Ports	Standard: USB Device, USB Host; PASS/FAIL, LA interface, Multimeter interface, LAN and GPIB
Mathematics	Add, Subtract, Multiply, FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Display	Digital Multimeter and Logic Analyzer

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey
Product Net Weight	3.8kg (Excluding packaging)
Product Size	330mm x 165mm x 165mm
Standard Accessories	Probe x 2 (1x, 10x switchable), Logic Analyzer Probe UT-P06, Current-to-Voltage Converter module, (UT-M03, UT-M04) Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	540 x 425 x 325mm (0.063 CBM Per Export Carton)
Standard Carton Gross Weight	Around 13.7kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD4202C**Digital Storage Oscilloscope****SPECIFICATIONS**
[Enlarge](#)

Feature	UTD4202C
Bandwidth	200 MHz
Rise Time	≤1.8 ns
Sample Range	2GS/s
Vertical Sensitivity	2mV ~ 5V/div
Record Length (Max)	1024k
Sample Rate	Real time 2GS/s, Equivalent: 50GS/s
Scan Time Base	2ns ~ 50s/div
Trigger Type	Edge, Pulse, Video, Slope and LA
Automatic Waveform Measurements	27
Ports	Standard: USB Device, USB Host; PASS/FAIL, LA interface, Multimeter interface, LAN and GPIB
Mathematics	Add, Subtract, Multiply, FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Display	Digital Multimeter and Logic Analyzer

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz - 440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey
Product Net Weight	3.8kg (Excluding packaging)
Product Size	330mm x 165mm x 165mm
Standard Accessories	Probe x 2 (1x, 10x switchable), Logic Analyzer Probe UT-P06, Current-to-Voltage Convertor module, (UT-M03, UT-M04) Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	540 x 425 x 325mm (0.063 CBM Per Export Carton)
Standard Carton Gross Weight	Around 13.7kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)

UTD4302C
[Enlarge](#)
[Download Manual](#)
[Download Software](#)
Digital Storage Oscilloscope**SPECIFICATIONS**

Feature	UTD4302C
Bandwidth	300 MHz
Rise Time	≤1.2 ns
Real-time Sampling Rate	2GS/s
Equivalent Sampling Range	50GS/s
Vertical Sensitivity	2mV ~ 5V/div
Record Length (Max)	1024k
Scan Time Base	1ns ~ 50s/div
Trigger Type	Edge, Pulse, Video, Slope and Alternate
Automatic Waveform Measurements	27
Frequency Counter	6 digits frequency counter
Ports	Standard: USB Device, USB Host; PASS/FAIL, LA interface, Multimeter interface, LAN and GPIB
Mathematics	Add, Subtract, Multiply, Divide, Reverse and FFT
Applications	College Education, R&D, Electronic product assemble line, Industrial Control etc.
Other Features	Digital Multimeter and Logic Analyzer

GENERAL CHARACTERISTICS

Power	100 - 240VACRMS, 45Hz -440Hz, CAT II
LCD Size	Diagonal 145mm (5.7 inches)
Product Color	Red and Grey
Product Net Weight	3.8kg(Excluding packaging)
Product Size	330mm x 165mm x 165mm
Accessories	Probe x 2 (1x, 10x switchable), Logic Analyzer Probe UT-P06, Current-to-Voltage Convertor module, (UT-M03, UT-M04) Power Cord and English Manual
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	2 pcs
Standard Carton Measurement	540 x 425 x 325mm (0.063 CBM Per Export Carton)
Standard Carton Gross Weight	Around 13.7kg

Specifications and other information are subject to change without further notice.

[Back to main menu](#)