



HX601B Pressure Calibrator

- ◆ Pressure range: : (-1-0)bar, (0-2500)bar (any range within these two range)
- ◆ Accuracy: : $\pm 0.05\% \text{F.S}$
- ◆ Voltage measurement: : (0-25)V Accuracy: $\pm(0.02\% \text{R.D} + 0.005\% \text{F.S})$
- ◆ Current measurement: (0-25)mA Accuracy: $\pm(0.02\% \text{R.D} + 0.005\% \text{F.S})$

Product Description

HX601B Intelligent Pressure Calibrator has the double-line large screen with backlight function. It can meet customers' requirement in the 5-digit display and 9 pressure units. It provides pressure measurement for calibrating pressure (differential pressure) transmitters, precision (general) pressure gauges and other pressure instruments. It has been used in the industries of power, chemical, petrol, metallurgy, metering, etc.

Features

- ◆ Equipped with rugged aluminum alloy cover
- ◆ Pressure-transmitting medium including air, oil, and water
- ◆ 5-digit LCD screen with backlight
- ◆ 9 Pressure Units Selectable: kPa, Pa, psi, kgf/cm², bar, mbar, mmH₂O, mmHg, MPa.
- ◆ Zero point, full scale calibration function
- ◆ Lithium battery inside and special adapters
- ◆ Overload and short circuit protection
- ◆ Light weight, small size, easy operation
- ◆ Rapid in operation, compatible with computer software
- ◆ Support Hart Version 5

Technical specification

- ◆ Range(-1-0)bar,(0-2500)bar(any range within this two range)
- ◆ Accuracy: $\pm 0.05\% \text{F.S}$
- ◆ Current measurement: (0-25)mA Accuracy: $\pm(0.02\% \text{R.D} + 0.005\% \text{F.S})$
- ◆ Voltage measurement: (0-25)V Accuracy: $\pm(0.02\% \text{R.D} + 0.005\% \text{F.S})$
- ◆ Temperature compensating range:(0-50)°C
- ◆ DC output:DC24V($\leq 30\text{mA}$) Accuracy: $\pm 1\% \text{F.S}$
- ◆ Power supply: Lithium battery power supply or special adapter
- ◆ Connection: M20×1.5 or 1/4"NPT male thread(or customized)
- ◆ Dimensions: $\Phi 95\text{mm} \times 50\text{mm}$. Total Height:150mm
- ◆ Weight:0.75kg