

DIGITAL TORQUE WRENCH



- Clockwise and counter-clockwise operation
- Unit: N.m, in.lb, ft.lb, kg.cm
- Peak and track working mode
- Target torque value can be set, with audible and visible alarm:
8 green LED light on and buzzer sounds when target torque value is approached
4 red LED light on and buzzer sounds when target torque value is reached
- Power off automatically in 5 minutes without any operations
- Non-slip grip handle
- With overload record (once the torque reaches 110% of the maximum range)
- Supplied with calibration certificate

SPECIFICATION

Code		IST-W30A	IST-W135A	IST-W200A	IST-W340A	IST-W500A	IST-W850A
Range		6~30N.m	27~135N.m	40~200N.m	68~340N.m	100~500N.m	170~850N.m
Accuracy	clockwise	±2%	±2%	±2%	±2%	±2.5%	±2.5%
	counter-clock wise	±3%	±3%	±3%	±3%	±3.5%	±3.5%
Resolution		0.01N.m	0.1N.m	0.1N.m	0.1N.m	0.1N.m	0.1N.m
Lever-type ratchet (L)		1/4"	3/8"	1/2"	1/2"	3/4"	3/4"
Power supply		2xAA batteries, for 110 hours working					
Length		390mm	415mm	530mm	650mm	950mm	1220mm
Weight		830g	950g	1400g	1600g	2100g	2550g

OPTIONAL ACCESSORY

Calibration cable	IST-W-CABLE
-------------------	-------------