

Technical Data Sheet

Pressure / Temperature / Humidity / Air Velocity / Airflow / Sound level

Kimo Kigaz 200 STD Combustion Gas Analyzer Kimo Kigaz 200 PRO Combustion Gas Analyzer

CE

KIGAZ 200 COMBUSTION GAS ANALYSER



Interchangeable O₂, COH₂,
NO et CH₄ sensors



Supplied with magnetic
protective cover



TÜV-SÜD Approved
EN50379 - 1&2
(\$5.5 / \$5.6 / \$5.7)



KEY POINTS



CO sensor protection by
solenoid valve



Autozeroing in the flue

- CO sensor protection by solenoid valve
- LED on probe handle to light dark areas
- Single connector

- Step-by-step procedure (gas flow...)
- Integrated printer
- Interchangeable duct
- 2 Go of memory (100 000 measurements)

INSTRUMENT FEATURES

GAS	- Autozero in the flue - CO sensor protection by solenoid valve	Flue gas CO and ambient CO max	Interchangeable sensors : O ₂ and CO-H ₂ and NO and CH ₄ (optional)	Excess air Losses	Efficiency > 100%
PRESSURE	Differential pressure measurement	Draft measurement			
TEMPERATURE	Ambient temperature	Flue gas temperature	Delta Temperature	DHW temperature 2 thermocouples	Dew point temperature
OTHERS FUNCTIONS	15 programmed combustible ¹	Adding 5 combustibles by the user	Automatic measurement	Opacity index	

¹Combustibles : Sahara/Fos-sur-Mer Natural Gas, Groningen Natural Gas, Russia/North Sea Natural Gas, Propane, LPG, Butane, Light Oil, Heavy Oil, Bituminous coal, Hard coal, Coke gas, Bio fuel 5%, Wood 20%, Wood-chip 21%, Pellet 8%

MEASUREMENT RANGES

Parameter	Sensor	Measuring range	Resolution	Accuracy*	T ₉₀ response time
O ₂	Electro-chemical	From 0% to 21%	0.1% vol.	±0.2% vol.	30 s
CO (with H ₂ compensation)	Electro-chemical	From 0 to 8000 ppm	1 ppm	From 0 to 200 ppm : ±10 ppm From 201 to 2000 ppm : ±5% of measured value From 2001 to 8000 ppm : ±10% of measured value	30 s
NO	Electro-chemical	From 0 to 5000 ppm	1 ppm	From 0 to 100 ppm : ±5 ppm. From 101 to 5000 ppm : ±5% of measured value	30 s
NO _x	Calculated**	From 0 to 5155 ppm	1 ppm		
CO ₂	Calculated**	From 0 to 99% vol	0.1% vol		
CH ₄	Semiconductor	From 0 to 10000 ppm From 0 to 1% Vol From 0 to 20 %LEL	1 ppm 0.0001% Vol 0.002%LEL	±20% of full scale	40 s
Flue gas temperature	K thermocouple	From -100 to +1250 °C	0.1 °C	±1 °C	45 s
Ambient temperature	Internal NTC	From -20 to +120 °C	0.1 °C	±0.5 °C	
Ambient temperature	Pt100 (1/3 Din external probe)	From -50 to +250 °C	0.1 °C	±0.3% of measured value ±0,25 °C	30 s
Dew point temperature	Calculated**	From 0 to +99 °Ctd	0.1 °C		
DHW temperature	TcK (external probe)	From -200 to +1300 °C	0.1 °C	±1 °C	
Differential pressure Draft	Piezoelectric	From -20 000 to +20 000 Pa	1 Pa	From -20 000 to -751 Pa : ±(-0.5% of measured value +4.5 Pa) From 750 to -61 Pa : ±(-0.9% of measured value +1.5 Pa) From -60 to 60 Pa : ±2 Pa From 61 to 750 Pa : ±(0.9% of measured value +1.5 Pa) From 751 to 20 000 Pa : ±(0.5% of measured value + 4.5 Pa)	
Losses	Calculated**	From 0 to 100%	0.1%		
Flue gas velocity		From 0 to 99.9 m/s	0.1 m/s		
Excess air (λ)	Calculated**	From 1 to 9.99	0.01		
Efficiency (η _s)	Calculated**	From 0 to 100%	0.1 %		
Efficiency (η _t) (condensation)	Calculated**	From 0 to 120%	0.1%		
Opacity index	External instrument	From 0 to 9			

*All accuracies indicated in this document were stated in laboratory conditions and can be guaranteed for measurements carried out in the same conditions, or carried out with required compensation.


**Calculation is made based on the measured values by the analyzer.

TECHNICAL FEATURES

	Features
Dimensions	Instrument : 331 x 112 x 86 mm Flue gas probe : 300 mm Cable length : 2.50 m
Weight (with battery)	1160 g
Display	Grey scale 3.5" display
Keypad	Rotating button ; 3 function keys + OK key ; Backlighted keypad
Material	Housing and probe : ABS ; Probe cable : neoprene
Protection	IP40
PC interface	Bluetooth® (optional) ; USB
Power supply	Li-Ion battery 3.6 V 4400 mA
Battery life	10 h in continuous operating
Use temperature	From +5 to +50 °C
Storage temperature	From -20 to +50 °C

MENUS / ACTIVE VIEWS / APPLICATION


Analyser menus



Example of analysis



DHW network temperature



Ambient CO checking

INSTRUMENT DESCRIPTION
> Overview

> Connections

 External probes connection
 (Pt100 temperature, CH₄...)


Thermocouple connections

Top view

Flue gas connection



P- pressure plug

P+ pressure plug

Bottom view
actoolsupply.com
 Power supply
 connection
USB
connection

Right side view

SUPPLIED WITH


Model	KIGAZ 200 STD	KIGAZ 200 PRO
Supplied with		
Number of interchangeable sensors	2 (O ₂ and CO-H ₂)	3 (O ₂ , CO-H ₂ and NO)
Scalable	yes : NO or CH ₄	Yes : CH ₄
Calibration certificate	yes	yes
Transport bag	yes	yes
Flue gas probe and its water trap	yes	yes
Magnetic protective cover	yes	yes
Differential pressure kit	yes	yes



Transport bag

SOFTWARE

Analysers are supplied with LIGAZ software allowing database creation (Customers, Boilers, inspections), downloading and printing inspections and analyser configuration.



ACCESSORIES*

SCOT : Ambient CO probe

SCO2T : Ambient CO₂ probe

SPA 150SP : Ambient Pt100 probe

SKCL 150 : Thermocouple probe with lamella

SCI : Ionisation current measurement probe

SDFG : Gas leak detection probe (CH₄)

PSK-180 : Flue gas probe with interchangeable contact tip, **180 mm** length, up to **500 °C**

PSK-300 : Flue gas probe with interchangeable contact tip, **300 mm** length, up to **500 °C**

PSK-750 : Flue gas probe with interchangeable contact tip in INCONEL, **750 mm** length, use up to **1100 °C**

PSK-1000 : Flue gas probe with interchangeable contact tip in INCONEL, **1000 mm** length, up to **1100 °C**

KEG : Gas network tightness kit

PMO : Opacity pump

Bluetooth® module : Data downloading and instrument configuration

LOGAZ : Software allowing database creation (customers, boilers and inspections), inspections downloading and printing, customizable procedure reports creation, inspection planning, on-site service contracts management (operator planning, customer care) and real-time measurements visualization and recording



Ionisation current probe



Gas leak probe



Gas network tightness kit

¹Please see the technical datasheet of accessories for kigaz for further details