


Programmable Temperature & Humidity Controller

TH500



- High Accuracy Control
- History management
- 300 pattern setting
- Temperature & Humidity PID group
- Convenient communication data management
- Various output type

Programmable Temperature & Humidity Controller

CONVENIENT SETTING BY TOUCH PANEL TYPE

FEATURES

- High Accuracy Control
- History management
- 300 pattern setting
- Temperature & Humidity PID group
- Convenient communication data management
- Various output type(20 points)

Input		
Input signal	Temperature	RT,DPT100 Q, DIN43760)
	Humidity	4~20 mA d.c(I - 5 V d.c)
	Sampling time	500 ms
Measuring range	Temp. range	-100.00 ~ 200.00 °C
	Humi. Range	0.0 ~ 100.0 %RH
Accuracy	Temp. side	±0.1 % (Max. range)
	Humi. side	±1 % (Max. range)
Contact input(D/I)		8 points(1a 4 points×2), 8V d.c 10 mA Max
Allowable line resistance	R, T, D	10 Q max/1 line
Input resistance	DV voltage input Approx.	1M(At V d.c)
Allowable signal impedance	DV voltage input Approx.	2ko max


Communication		
Interface Standard	EIA-RS232, 485, USB V1.1	
Max. connection lines	RS232	1:1
	RS485	1:32(Address 1~999)
Communication type	RS232	Full Duplex
	RS485	4 lines Full Duplex / 2lines Half Duplex
Synchronization	RS232/485	Synchronous mode
Communication distance	USB V1.1	Approx. 10 m
	RS232	Approx. 10 m
	RS485	Approx. 12 km
Communication speed (Kbps)	USB V1.1	Approx. 12 Mbps
	RS232/485	9.6 / 19.2 / 38.4 / 57.6 / 115
Data Length	RS232/485	7/8 Bits
Parity Bit	RS232/485	NONE / EVEN / ODD
Stop Bit	RS232/485	1 / 2 Bit(s)
Protocol	USB V1.1	Bulk Mode
	RS232/485	PC/LINK / PC/LINK+CRC
Response Time	RS232/485	0~9.999 (×10.0μs)

Output		
Contact output (DO)	Relay contact 12 points	NO : 30 V d.c 5 A Max, 250 V a.c 5 A Max. NC : 30 V d.c 1 A Max, 250 V a.c 2 A Max.
	Open collector 8 points	24 V d.c 300 mA Max.
Control output	S.S.R	ON : 24 V d.c Pulse voltage(Resistive load Min, 800 Q) OFF : 0.1 V d.c Max, Cycle time : 1 ~ 1,000 sec Output limit : 0.0 ~ 100.0 % Resolution : 0.1 % or 10 ms whichever is smaller
	Current output	4 ~ 20 mA d.c (3.2 ~ 20.8 mA d.c) Renewal time : 500 ms Resistive load : 600 Q max Output limit : -5.0 ~ 105.0 %
Retransmission output	Current output	4.0 ~ 20.0 mA d.c
	Renewal time	500 ms
	Resistive load	600 Q max
	Output limit	-5.0 ~ 105.0 %
	Output type	Process value(PV), Set value(SV), Output volume(MV) selectable
Accuracy		S.S.R control output : ±0.1% of F.S Resolution : Approx.1,000
		Current control output : ±0.025 % of F.S Resolution : Approx. 4,000

Operation Environment	
Ambient temperature	0 ~ 50 °C
Ambient humidity	20 ~ 90 %RH(No condensation)
Storage temperature	-25 °C ~ 70 °C
Storage humidity	5 ~ 95 %RH(No condensation)
Insulation resistance	20 MΩ Min(Between 1st ~ 2nd ~ Ground, 500 V d.c)
Dielectric strength	2500 V a.c(Between 1st ~ 2nd ~ Ground), 1 minute
Vibration resistance	10 ~ 55 Hz, Width 0.75 mm, 3 directions 4 times, 5 minute/cycle
Shock resistance	147 m/s ² , 3 directions 3 times
Dimensions	183(W)×144(H)×94(D)
Weight	Approx. 2.35 kg(in packing condition)

Operation screen

After you finish to connect & turn on the power, The operating screen will be shown as below. Select a proper screen among 3 types.



The 1st Operation screen

The 2nd Operation screen

Graph display screen

Error Display screen

The indication of errors through sensor disconnection and external DI is displayed in the operating record indication screen.

Run history		NEXT	ESC
05-04	09:32:44	T. SENSOR BURNOUT	
05-04	09:32:44	H. SENSOR BURNOUT	
05-04	09:44:32	FIX-RUN START	
05-04	09:44:34	RESET BY T. BURNOUT	
05-04	09:45:02	FIX-RUN START	
05-04	09:45:03	RESET BY T. BURNOUT	
05-04	11:33:43	T. SENSOR BURNOUT	
05-04	11:35:43	H. SENSOR BURNOUT	
05-04	11:38:15	FIX-RUN START	
05-04	11:38:17	RESET BY H. BURNOUT	

Operating record screen



Supply voltage


Power supply : 100 – 240 V a.c.
Frequency : 50 – 60 Hz
Power consumption : 20 VA

Display

Screen standard : Color STN LCD (115.17 × 86.37 mm)
Number of Pixels : 320X240 Pixel, 256 Colors
Back light : CCFL
Life of back light : Approx. 20,000hrs.
Touch type : 4 wire resistive touch screen
Language : English

PID setting group

The TH500 is equipped with the total 16 PID ZONES. As shown in the chart below, the four temperature zones and four humidity zones are combined with each other.



Manu screen

Menu screen is consist of function setting menu, system setting menu, program setting menu and convenient to set.



Function setting menu



Program setting menu



System setting menu

Contact input(D/I) & Contact output(D/O)

Contact input is consist of 8 points and indicated in English. Also, contact output is consist of 20 points(Relay 12 points/ Open collector 8 points). The contact output can appoint an inner signal output, time signal, alarm output, output by basic operating, increase, maintenance or decrease of temp. and humi and output for each section.

Function

Measuring input	Bias	Temperature 1 point : -100.00 ~ 1000.00 °C Humidity 1 point : -100.0 ~ 100.0 %RH
	Scaling	DC voltage(V d.c) : According to convert range
	Input filter(LPF)	2 ~ 180 second
Control action	Pattern	300 Pattern
	Segment	6,000 Segment(100 segment / 1 pattern)
	P.I.D Group	16 group(Temp. 4 zone× Humi. 4 zone)
	Auto tuning	According to set value, auto tuning is operating
	Proportional band	0.00 ~ 100.00 % (In case of 0.00 %, ON/OFF control)
	Integral time	0.0 ~ 6,000 sec(0 sec = OFF condition)
	Derivative time	0.0 ~ 6,000 sec(0 sec = OFF condition)
	ON/OFF control	Proportional Band (P) is 0
Retransmission output	Direct/Reverse action	Select Direct or Reverse action in control output
	ON/OFF Hysteresis	0.1 ~ 300.0 (°C) (In case of Humidity, Temperature of Humidity or conversion value)
	Fuzzy	Select ON/OFF
Retransmission output	Signal	Process value(PV), Set value(SV), Manipulated Value(MV) selectable
	Scaling	Auto scaling (4 ~ 20 mA d.c)
Alarm	Setting alarm	System alarm : 4 points *Setting range : 0.1 ~ 100.0 % 4points / 1 pattern, ON/OFF settable for each segment
	Type of alarm	High / Low deviation alarm etc. 20 types of alarms
	Process alarm	Temperature : -100.00 ~ 200.00 °C Humidity : 0.0 ~ 100.0 % RH
	Deviation alarm	Temperature : -300.00 ~ 300.00 °C Humidity : -100.0 ~ 100.0 % RH


Pattern setting

Set a segment for each pattern as below.



Graphic screen display


Because all saved Data file is in text mode, you can see the content of saved data file with any editor, word-processor or Excel.




Graphic display screen

● Connection Diagram


• UNIT BODY




• SEPARATE BODY




• SEPARATE BODY I/O BOARD 1



• SEPARATE BODY I/O BOARD 2



• SEPARATE BODY I/O BOARD 3




● Approval Standards

Safety : UL61010 (Under process)


CE : EN61010-1 (Under process)

● Model and Suffix code




Model	Suffix code	Description
TH500	☐ ☐ ☐	TEMPERATURE-HUMIDITY PROGRAMMABLE CONTROLLER
Type	N	None
	1	UNIT BODY Sensor input : Temperature (Pt100Ω / 0 - 5 V dc) Humidity (Pt100Ω / 0 - 5 V dc) Digital input (D/I) : 8 points Control output : Temperature (SCR/SSR 1 point), Humidity (SCR/SSR 1 point) Retransmission : Temperature (4 - 20 mA dc 1 point), Humidity (4 - 40 mA dc 1 point) Contact output : Relay (1a1b) 4 points, Relay (1a) 8 points Transistor output : Open Collector 8 points COMMUNICATION : RS232C, RS485, USB
	2	SEPARATE BODY Sensor input : Temperature (Pt100 Ω / 0 - 5 V dc) Humidity (Pt100 Ω / 0 - 5 V dc) Retransmission : Temperature (4 - 20 mA dc 1 point) Humidity (4 - 40 mA dc 1 point) Communication : RS232C, RS485, USB
Option	N	None
	1	I/O BOARD 1 SMPS (24 V dc, 18 W) + D/I 8 points + RELAY (1a1b : 4 + 1a : 8) 12 points
	2	I/O BOARD 2 O.C 8 points
	3	I/O BOARD 3 Relay(1a1b) 8 points I/O BOARD 1 + I/O BOARD 2
	4	SMPS (24 V dc, 18 W) + D/I 8 points + Relay (1a1b : 4+1a:8) 12 points + O.C 8 points I/O BOARD 1 + I/O BOARD 3
	5	SMPS (24 V dc, 18 W) + D/I 8 points + Relay (1a1b:4+1a:8) 12 points 12 points + Relay(1a1b) 8 points
Communication	N	None
	1	ETHERNET (Preparing)

● Dimension (Unit : mm)



● Panel cutout (Unit : mm)





HANYOUNG NUX CO., LTD.

1381-3, Juan-Dong, Nam-Gu Incheon, Korea
TEL: (82-32) 876-4697 FAX: (82-32) 876-4696
Http://www.hynux.com E-mail: hyelec01@hynux.com

All specifications are subject to change without prior notice, and when you place order, please consult HANYOUNG NUX CO., LTD.

www.hynux.net

