

UT207


[Enlarge](#)
[Download Manual](#)

Digital Clamp Multimeters

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	6.6V/66V/600V	$\pm (0.8\%+1)$
AC Voltage	6.6V/66V/600V	$\pm (1.2\%+5)$
DC Current	66A/1000A	$\pm (1.5\%+8)$
AC Current	66A/1000A	$\pm (2\%+8)$
Resistance	660 Ω /6.6k Ω /66k Ω /660k Ω / 6.6M Ω /66M Ω	$\pm (1\%+2)$
Temperature	-40 $^{\circ}$ C~1000 $^{\circ}$ C -40 $^{\circ}$ F~1832 $^{\circ}$ F	
Frequency	660Hz/6.6kHz/66kHz/660kHz/ 6.6MHz/66MHz	$\pm (0.1\%+3)$
Special Functions		
Auto Ranging		✓
Diode		✓
Continuity Buzzer		✓
True RMS	AC Voltage	✓
Surge Current	AC Current	✓
Max/Min Mode		✓
Data Hold		✓
Sleep Mode		✓
Display Backlight		✓
Full Icon Display		✓
Low Battery Display		✓
Input Impedance for AC Voltage Measurement	Around 10M Ω	✓
Max. Display	5999	✓

GENERAL CHARACTERISTICS

Power	9V Alkaline Battery (1604A)
LCD Size	47 x 30 mm
Product Color	Red and Grey
Product Net Weight	533g
Product Size	285 x 105 x 45 mm
Standard Accessories	UT207 - Test Lead, Alkaline Battery, English Manual, Carrying Bag
Standard Individual Packingt	Gift Box
Standard Carton Gross Weight	24 pcs
Standard Carton Gross Weight	610 x 360 x 305 mm (0.067 CBM Per Standard Carton)
Standard Carton Gross Weight	25kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)