

UNI-T UT118A

Pen Type Digital Multimeters



Specifications	Range		Best Accuracy
Model	SCAN Mode	AUTO Mode	UT118A
DC Voltage (V)	3V/30V/300V	3V/30V/300V	±(1%+3)
AC Voltage (V)	3V/30V/300V	3V/30V/300V	±(1%+4)
Resistance (Ω)	300Ω/3kΩ/30kΩ/300kΩ/3MΩ	300Ω/3kΩ/30kΩ/300kΩ/3MΩ/30MΩ	±(1%+3)
Capacitance (F)	3nF/30nF/300nF/3μF/30μF/300μF	3nF/30nF/300nF/3μF/30μF/300μF/3mF	±(3%+5)
Features			
Display Count			3000
Auto Range			√
Diode			√
Auto Power Off	Around 10 Minutes		√
Continuity Buzzer			√
Low Battery Indication			√
Data Hold			√
MAX Mode			√
MIN Mode			√
LCD Backlight			√
Penlight			√
Input Impedance for DCV	≥10MΩ		√
General Characteristic			
Power	3V Li-MnO2 Cion Cell Battery		

LCD Size	28mm×14mm
Product Color	Red and Grey
Product Net Weight	90g
Product Size	20mm×27mm×182mm
Standard Accessories	Battery, Test Lead
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	80 PCs
Standard Carton Measurement	570mm×300mm×415mm (0.071 CBM Per Export Carton)
Standard Carton Gross Weight	12.5Kg