



EN:61010-1
EN:61326-1
EN:61010-2-032



■ UT273



■ UT275

SPECIFICATIONS



Specifications	Range	Best Accuracy	
		UT273	UT275
Model			
Earth Ground Resistance (Ω)	0.01~0.099Ω	±(1%+0.01)	±(1%+0.01)
	0.1~0.99Ω	±(1%+0.01)	±(1%+0.01)
	1.0~49.9Ω	±(1.5%+0.1)	±(1.5%+0.1)
	50.0~99.5Ω	±(2%+0.5)	±(2%+0.5)
	100~199Ω	±(3%+1)	±(3%+1)
	200~395Ω	±(10%+5)	±(10%+5)
	400~590Ω	±(20%+10)	±(20%+10)
Leakage Current(A)	600~1000Ω	±(25%+20)	±(25%+20)
	0.00~299mA		±(2.5%+2mA)
	0.30~2.99A		±(2.5%+100mA)
	3.00~30.0A		±(2.5%+300mA)
Features			
Display Count		9999	9999
Auto Range		✓	✓
Jaw Capacity		28mm	28mm
Auto Power Off		✓	✓
Low Battery Indication	≤5.2V		
Data Hold		✓	✓
Data Logging		30	30
Data Recall		✓	✓
LCD Backlight		✓	✓
Auto Calibration		✓	✓
Resistance Limit Alarm		✓	✓

GENERAL CHARACTERISTICS

Power	1.5V Alkaline Batteries (LR6) ×4
LCD Size	47mm × 28.5mm
Product Color	Red and Grey
Product Net Weight	1320g
Product Size	293mm × 90mm × 66mm
Standard Accessories	Batteries, Test Ring, Tool Box
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	5 PCs
Standard Carton Measurement	495mm × 368mm × 310mm (0.057CBM Per Standard Carton)
Standard Carton Gross Weight	16Kg