



BENETECH GM3125 High-voltage Insulation Resistance Tester

FEATURES

- Elegant appearance and compact size
- High accuracy with 5% differences up and down
- Feature protective function of voltage overload
- Ergonomic design is comfortable to manipulate
- LCD backlight display function
- Low battery indication is energy-saving
- Auto power off function



Specifications

Display	Max. 999 Counts LCD Display
Over Range Indication	OL Mark Appears on Insulation Resistance Range
Sample Rate	0.5~10 times/sec
Operable Altitude	Less than 2000m
Operable Circumstance	Temperature 0~40°C, Humidity ≤ 85%
Storage Circumstance	Temperature -20~60°C, Humidity ≤ 90%
Voltage Resistance	AC8320(50/60Hz)/5 second
Power Supply	DC 12V(8x1.5V LR14 B battery)
Dimensions	6.02 x 3.78 x 7.87" / 15.3 x 9.6 x 20cm (LxWxH)
Weight	116.05 oz / 3290g

Package Includes

- High Vage Insulation Tester
- 1 x Red High Voltage Test Wire
- 1 x Green Test Wire
- 1 x Black Test Wire
- 1 x Alligator Clip
- 1 x 1.5V LR14 Alkaline Battery
- 1 x Manual
- 1 x Soft Bag