

# PLB 150/250 Portable Liquid Baths



The PLB series are portable liquid baths ( Portable Temperature Calibrators) designed and manufactured by EiUK, a market leader in temperature calibration. Stirred liquid baths are suitable for calibrating temperature sensors of all size and diameters an shape with-out the need of specifically drilled block. They also provide much smaller calibration uncertainty than Dry Block

PLB large calibration volume 60x170 mm make it ideal for use as Portable liquid Bath. PLB series can be converted into a Dry Block Temperature Calibrator and in conjunction with our range of multi-functional accessories they can be use as Infrared Calibrator source, Surface Temperatures Calibrators and Dry block calibrator- The Large insert 60x170 mm make it possible to calibrate multiple sensors at the same time. PLB are available in 2 different models to cover a range from -32 to 250 Deg C

### Accuracy $\pm 0.08^{\circ}\text{C}$

Down to  $\pm 0.08^{\circ}\text{C}$  using our external reference sensor and special calibration with built-in reference sensor input

### Excellent stability $\pm 0.01^{\circ}\text{C}$

New controller and block design

### Built-in dual channel readout ( TC version)

Read simultaneously external reference sensor and unit under test

### Wider temperature range

PLB 150 from  $-32$  to  $140^{\circ}\text{C}$  (from ambient)  
PLB 250 from amb to  $250^{\circ}\text{C}$

### Large Calibration volume 60x170 mm

Perform even larger diameter sensor calibration

### Use as Dry Block, Black Body Source or Zero Reference

Unique range of multifunctional insert to extend the range of application

### Fast heating/cooling time and light weight

Save time and money

	TS VERSION	TC VERSION
liquid BATH	●	●
Use as a Dry block	●	●
Removable Insert	●	●
Infrared Insert	●	●
Surface Sensor Insert	●	●
Zero Reference Insert	●	●
Multi-Holes Inserts	●	●
Dual Line Display	●	●
Digital Communication	●	●
Stand Alone thermostat testing	●	●
Configurable C, F, K	●	●
RTD's Input		●
Universal Thermocouple's Input		●
Reference Sensor Input		●
Reference sensor linearization matching		●

# PLB 150/250 Portable Liquid Baths



## SENSOR UNDER TEST INPUT

The TC version is equipped with a dual input which can measure the most common Thermocouples and RTD (3-4 WIRES) sensor- It eliminates the need to carry another Thermometer in the Field for calibrating the unit under test. Direct comparison of the unit under test and the Internal or External reference sensor is visualised on the display



## HIGH ACCURACY (PLB-TC-OPT-01)

The TC version is equipped with an built-in high accuracy reference input to be used in conjunction with our SRS( semi-standard PRT)- This feature allows the PTB-TC to perform calibration with an higher degree of accuracy.- It also eliminates most of the error due to Stem conduction and different load

A special 90C angled external reference sensor is designed to accommodate calibration of sensors with transmitter head- It provide maximum clearance to the top of the calibrator-

Our SRS external reference sensors are especially designed to improve the performance of our PTB series- The size and length of the external reference sensors have been chosen to provide best performance on the PTB series- A special linearization/calibration with the built-in reference input provide maximum reading accuracy as good as 0.08 Deg C. The internal and reference sensor are independent from each other.

## AUTO RAMP/STEP

Programmable AUTORAMP function is available directly from Keyboard- User can select number of cycles, minimum and maximum points and temperature gradient. The function is ideal for automatic calibration of thermo switches. An AUTO STEP function with programmable STEP value and HOLD VALUE between each SETP is also available when using PLB connected with our EiUK-CAL software

## SWITCH TEST

Both the PLB-TS and PLB-TC versions are equipped with a " switch test input" which provide facility to perform automatic switch test calibration. PTB will log both the "Open"and "Close" for onsite recall and dead band calculation

## CALIBRATION SOFTWARE

### EiUK- CAL

TS series are supplied in the standard delivery with our Powerful EiUK-Cal software package-

### Temperature Sensor Calibration both automatic and manual

Automatic Calibration routine for all type of temperature sensors with advanced feature such reference sensor stabilization time- Calibration data are automatically populated and stored for printing calibration report- This procedure can also be ran in manual mode to allow the operator to manually enter the data- This is particular useful when calibrating Temperature device such digital thermometer or analogue thermometers

### Stress Test

Simply set the MAX and MINI value and the software will run an automatic Stress Test of one single sensor or a batch-

### Advance Thermostat Calibration

Simply set the open and close temperature limits, type of thermostat, type of test and T will automatically run the test- This is available on both the TC and TS version

### Multiple Sensor Calibration

When use in conjunction with our ATCS system up to 58 sensors can be calibrated automatically

# PLB 150/250 Portable Liquid Baths



## Technical Specifications

	PLB 150	PLB 250
Temperature Range @ 20 °C	-12 °C to 140 °C ( at ambient @ 20 °C )	Amb C to 250 °C
Stability	± 0.01 °C	± 0.02 °C
Time to Stability	10 min approx	
Radial Uniformity	± 0.01 °C @ -10 °C ± 0.01 °C @ 0°C ± 0.02 °C @ 120 °C	± 0.01 °C @ 50 °C ± 0.03 °C @ 250 °C
Axial Uniformity ( Lower 40 mm )	± 0.02 °C @ -10 °C ± 0.02 °C @ 0°C ± 0.01 °C @ 120 °C	± 0.01 °C @ 50 °C ± 0.02 °C @ 180 °C ± 0.03 °C @ 250 °C
Accuracy ( Internal Sensor)	± 0.15 °C	± 0.15 °C
Accuracy with External SRS Reference Sensor* TC version only	± 0.08 °C	± 0.08 °C
Resolution	0.1 °C / 0.01 °C selectable	
Temperature units	C -F -K selectable	
Well Diameter	60 mm (54 mm as liquid bath)	60 mm(54 mm as liquid bath)
Immersion Depth ( as Dry block)	170 mm	170 mm
Immersion Depth ( as Liquid bath)	150 mm	150 mm
Heating Time ( including Stability)	ambient to 120°C: 30 min	20 to 250°C: 30 min
Cooling Time ( including Stability)	ambient to -10°C : 30 min	250 to 60°C: 60 min
Digital communication	RS232 ( USB converter)	
Switch test Input	12 VDC	
Thermocouple Input ( TC version Only)		
Type	K,N,R,S,J,E	
Range	0 C to 1300 °C	
Accuracy	± 1C Include CJC error	
Resolution	0.1 °C / 0.01 °C selectable	
RTD's Input ( TC version only)		
Type	Pt100 IEC 3/4 wires	
Range	-100 C to 700 °C	
Accuracy	± 0.3 °C	
Resolution	0.1 C / 0.01 °C selectable	
Voltage	115/230± 10%, 50/60 HZ	
Power	300 W	500 W
Weight	8 Kg	8 KG
Dimensions	160x340x330 mm	160x340x330

Specification for Stability, Huniformity and Temperature range based on use as Liquid Bath only  
 Specifications might change with-out prior notice  
 Standard Calibration certificate supplied with PLB 250 cover range from T ambient to 240 C

12 months period

\*Require SRS Reference sensor and UKAS calibration for probe matching linearization((PLB-TC-OPT-01)- Accuracy do not include long term sensor drift

# PLB 150/250 Portable Liquid Baths



## CONVERT TO DRY BLOCK CALIBRATOR

The PLB series use can be converted to a traditional Dry Block Temperature Calibrator extending its range of application. The large calibration volume of 54x150 make it possible to calibrate multiple sensors at the same time- A range of standard pre drilled dry inserts or custom made insert are available- All the inserts are made of aluminium, dimension 60 x170 mm



Part Number	Description
PLB-INS-01	Insert: Blank, PLB125/250- , Ø 60 x 170 mm
PLB-INS-02	Insert : PLB 150/250- Holes Ø 2 x4 -4.5-5.5-6.5-8.5-10.5-12.5mm
PLB-INS-03	Insert : PLB 150/250- Special ( please contact us)

## BLACK BODY TARGET

The PLB series use can be converted into an Infrared temperature calibrator by simply using the INFRARED BLACK BODY TARGET INSERT- The large well size 60 mm make it possible to calibrate Infrared thermometer with very large distance to Target to ratio with out compromising the accuracy

Each Insert is supplied with an angled Pt100 reference sensor to measure the true temperature at the bottom of the insert- The True temperature can be read directly on the Display of the TC version



Part Number	Description
PLB-INS-IR	Insert: Black Body target, PLB125/200. Size , Ø 60 x 170 mm,

## REFERENCE SENSORS SRS

Our range of semi standard reference sensors (SRS) are especially designed to improve the performance of our T series- The size and length of the external reference sensors have been chosen to These industrial platinum resistance thermometers are ideal for field and lab use. They are particularly designed for use as working standards in Dry Blocks and Liquid Baths . The 90 degree bent provide maximum clearance at the top of the calibrator allowing space for calibrating temperature sensors with head such transmitters- Size and dimensions are optimised for use with the T series series

### General specifications are:

Ro 100 ohm ± 0.05 ohm ( Pt 100 A Class)

Alpha 0.003850 ± 0.000005

Standard IEC 60751

Stability 0.010 ohm/year

Sensing Element length 15 mm

Metal Sheath

4 Wires Type

Supplied with 2 metre cable and connectors for TC version measurement input

Part Number	Range	Diameter	Immersion Depth	Application
SRS-PRT-03-A168B	-40 to 250 Deg			
SRS-PRT-45-A195B	-40 to 650 Deg C			
SRS-PRT-45-S480B	-40 to 650 Deg C			

# PLB 150/250 Portable Liquid Baths



## PLB STANDARD DELIVERY

PLB 150 and PLB 250 are supplied as standard with the full list of accessories

- PLB Portable Liquid Bath
- 500 CC of Silicon Oil 47V10 (PLB 150)
- 500 CC of Silicon Oil 47V50 ( PLB250)
- Closing Lead ( PLB-ACC-03)
- Fluid Empty System ( PLB-ACC-04)
- Thermometer Support ( PLB-ACC-05)
- Power Lead
- Fuse Kit
- Temperature switches test leads
- Traceable calibration certificate
- Instruction Manual
- Soft case with pocket and shoulder strap
- RS232 Cable
- EIUK- CAL Software Package

## SOFT CASE STANDARD DELIVERY

Robust soft case for transport with pockets for accessories and shoulder strap for easy transport- The case has 4 aluminium protective feet



## THERMOMETERS SUPPORT (PLB-ACC-05)

Hold Thermometer and Reference sensor in position while calibrating



Part Number				Description
				<b>Model</b>
PLB 150				PLB 150 Portable liquid Bath , - 12 to 140 C
PLB 250				PLB 250 Portable liquid Bath , - T amb to 250 C
				<b>version</b>
TS				Source Version without input
TC				Calibrator Version include Reference sensor input, sensor under test input
				<b>Power Supply</b>
115				115 V 50/60 Hz
230				230 Vac 50/60 Hz
				<b>Main Power Cable</b>
EU				Europe, 230
UK				UK 230
US/JP				USA/JP 110/115
PLB200	TC	230	UK	Example: PLB 250 TC version with 230 VAC, UK power lead

## HIGH ACCURACY OPTION (TC VERSION ONLY)

Part Number	Description
PLB-TC-OPT-01	SRS-PRT-03-A168B reference sensor and special UKAS calibration for linearization and probe matching- Range -12 to 250 Deg C

### Eurotron Instruments UK Ltd

Unit 13 Riley Close  
Royal Oak Industrial estate  
NN11 8QT  
www.eurotron-uk.com  
sales@eurotron-uk.com  
+44 (0) 1327 871044

