

TECHNICAL DATA

# Fluke Networks Pro3000™ Tone Generator



## Key features

- Send tone signal up to 10 miles (16 km) on most cables
- Analog tone generator with bed-of-nails clips
- SmartTone™ provides 5 distinct tones for exact pair identification
- Continuity testing and line polarity confirmation
- Tone can be traced by a compatible analog probe (sold separately)

## Product overview: Fluke Networks Pro3000™ Tone Generator

The Pro3000™ unfiltered toner, for use on inactive networks, uses SmartTone™ technology, with five different tones to allow the technician to easily identify individual pairs. Angled-bed-of-nails clips allow easy access to individual wires, and the RJ11 connector is ideal for use on telephone jacks.

## Specifications: Fluke Networks Pro3000™ Tone Generator

User interface	Slide switch selects Continuity or Tone Mode Push button switch selects SOLID, ALT or OFF Tone mode LED Continuity/Polarity LED
Solid Frequency	1000 Hz nominal
Alternating Frequency	1000/1500 Hz nominal
Over Voltage Protection	60 Vdc in Toner/Polarity Mode



Output Power in Tone Mode	8 dbm into 600 ohms
Output Voltage Level in Continuity Mode	8 Vdc with fresh battery
Battery	9V alkaline
Temperature	Operating: -20° C to 60° C, Storage: -40° C to 70° C
Case dimensions	2.7 in. x 2.4 in. x 1.4 in. (6.9 cm x 6.1 cm x 3.6 cm)

## Ordering information



### **26200900**

The Pro3000™ unfiltered toner, for use on inactive networks, uses SmartTone™ technology, with five different tones to allow the technician to easily identify individual pairs. Angled-bed-of-nails clips allow easy access to individual wires, and the RJ11 connector is ideal for use on telephone jacks.

Includes:

- Pro3000™ Analog Tone Generator"



**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Canada (800) 36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com](http://www.fluke.com)

©2022 Fluke Corporation.  
Specifications subject to change without notice.  
03/2022

**Modification of this document is not permitted  
without written permission from Fluke Corporation.**