

UNI-T®

UT262 SERIES

Non-Contact Phase Detectors

UT 262A ■ UT262C(NEW)



EN:61010-1



■ UT262A



■ UT262C

SPECIFICATIONS

Specifications	Range	UT262A	UT262C
Model			
Phase Sequence	[Positive Phase] indicated by four phase detecting lights turn on clockwise and non-continuous beeping sound. [Negative Phase] indicated by four phase detecting lights turn on anti-clockwise and continuous beeping sound.	✓ ✓	✓ ✓
Missing Phase Detection	R-S or S-T light Off	✓	✓
Live Power Detection	R-S or S-T light On	✓	✓
Circuit Break Detection	R-S or S-T light Off	✓	✓
Voltage Detection	R-S or S-T light On	✓	✓
AC Voltage Range(V)	70V~600V	✓	✓
Frequency Range(Hz)	40Hz~70Hz	✓	✓
Features			
Clamp Opening		Ø1.6~Ø16mm	Ø10~Ø400mm
Display Mode		LED	LED
Power on Indication		✓	✓
Buzzer Indication		✓	✓
Auto Power Off	Automatically switch off after three minutes	✓	✓

GENERAL CHARACTERISTICS

Power	1.5V Batteries (R6) × 2
Product Color	Red and Grey
Product Net Weight	180 g
Product Size	70mm × 75mm × 30mm
Standard Accessories	Batteries
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	20 PCs
Standard Carton Measurement	800mm × 300mm × 400mm (0.096 CBM Per Standard Carton)
Standard Carton Gross Weight	9 Kg