

UNI-T®

UT330 SERIES USB Datalogger

UT330A / UT330B / UT330C

NEW



EN 61326-1



UT330A



UT330B



UT330C

SPECIFICATIONS

USB

Specifications	Range	UT330A	UT330B	UT330C
Model				
Temperature(°C)	Range	-40°C~80°C(-40°F~176°F)	✓	✓
		0°C~40°C	±0.5°C	±0.5°C
	Accuracy	-30°C~0°C, 40°C~70°C	±1°C	±1°C
		-40°C~-30°C, 70°C~80°C	±2°C	±2°C
Relative Humidity	Resolution	0.1°C/0.1°F	✓	✓
	Range	0%RH~100%RH	✓	✓
	Accuracy	20%RH~80%RH	±3%RH	±3%RH
		<20%RH or >80%RH	±5%RH	±5%RH
Atmospheric Pressure	Resolution	0.1%RH	✓	✓
	Range	750hPa~1100hPa		✓
	Accuracy			±3 hPa
	Resolution	0.1hPa		✓
IP67		✓	✓	✓
°C/°F Selection		✓	✓	✓
Temperature Offset Settings		✓	✓	✓
Humidity Offset Settings			✓	✓
Pressure Offset Settings				✓
Data Logging		60000	60000	60000
Data Recall		✓	✓	✓
USB Interface		✓	✓	✓
Auto Record Time Setup		✓	✓	✓
User Name Settings		✓	✓	✓
Alarm Threshold		✓	✓	✓
Start Mode Setup		✓	✓	✓

GENERAL CHARACTERISTICS

Power	3.6V 1/2 AA Lithium Battery(ER14250) x 1
Product Color	Grey
Product Net Weight	52g
Product Size	122mmx30mmx24mm
Standard Accessories	Batteries, PC Software CD, Bracket, Screws
Standard Individual Packing	English Manual Batteries
Standard Quantity Per Carton	60 PCs
Standard Carton Measurement	575mm x 395mm x 250mm(0.056CBM Per Standard Carton)
Standard Carton Gross Weight	10.5Kg
Optional Accessories	Magnet Bracket (UT-B22)